



# OUTSTANDING COLOR QUALITY, HIGH PERFORMANCE, INTUITIVE USABILITY

The imageRUNNER ADVANCE C7500 Series brings outstanding image quality and fast, reliable performance to high-volume office environments. These intelligent systems are designed to work seamlessly with Canon's integrated software and services to provide a holistic solution for your business.

Print up to 80/70 ppm (BW/color)

Scan up to 240/220 ipm (300 dpi) (BW/color, duplex)

Print up to 13" × 19"

9,300-sheet maximum paper capacity

# Workflow Efficiency

- An intuitive user interface with a large, responsive, color touch-screen with smartphone-like usability helps make it easy to carry out tasks.
- My ADVANCE enables users to have a unique, customized experience that's tailored to their specific workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronized across multiple devices for consistency.
- Canon's MEAP platform supports a range of integrated solutions designed to simplify workflow and achieve a holistic business solution.
- Scalable support for mobile and flexible work styles can help increase efficiency by allowing workers to capture or print documents and access certain cloud applications.<sup>1</sup>
- Scan and convert documents to Searchable PDF, Microsoft<sup>®</sup> Word, and Microsoft PowerPoint<sup>®</sup> files through a single-pass, duplexing document feeder that holds up to 300 originals.
- Intelligent features, such as motion sensor technology to wake the device from Sleep mode and the ability to remove blank pages when scanning, can help maximize productivity.
- Create professional-looking reports, proposals, presentations, booklets, and newsletters with flexible finishing options such as professional punching, folding, document insertion, and booklet-making.
- The optional imagePASS print controller offers fast processing along with tools and utilities for producing professional-looking documents. The optional ColorPASS controller offers even more robust processing capabilities and additional graphic arts tools for color-critical environments.



Quality and Reliability

- Canon has employed proven engine technologies from the light production space to contribute to high-quality output, designed to meet the needs of demanding color environments.
- Produce consistently striking images with CV toner and outstanding imaging technologies, including Canon's V<sup>2</sup> color profile, up to 2400-dpi print resolution with R-VCSEL red laser technology, and a cooling system for the developer that helps maintain stable image quality over time.
- Employs Canon's signature reliability and is designed to help achieve maximum uptime with status notifications to help keep supplies replenished. These models also include intuitive user maintenance videos, the ability to replace toner on-the-fly, and automatic job rerouting (with optional solutions).



**Device and Fleet Management** 

- The ability to preconfigure devices makes installation easy and fleet management is simplified with the ability to synchronize settings across multiple devices.
- Canon's device management tools can provide a centralized point of control across an entire fleet, including the ability to check device status and consumables, turn off devices remotely, capture meter readings, and manage address books and printer drivers.
- Standard Genuine Adobe® PostScript® and PCL® support integration with enterprise applications and legacy systems to help streamline business processes.

# **Cost Management**

- The ability to apply print policies, monitor output, and restrict usage by user can help reduce unnecessary printing, enable cost recovery, and help save money on paper and toner.
- Tight integration with output management solutions, such as optional uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, contribute to maximizing uptime and can help reduce time spent by IT resolving issues.
- Consistent user operation, paired with remote and centralized fleet management, can help simplify IT management of a single device or fleet.


Security<sup>2</sup>

- Control device access by using the standard Universal Login Manager application.
- Help limit unauthorized distribution of sensitive information with an array of standard and optional document security features.
- Help facilitate information privacy and security by controlling access with IPsec, port filtering capabilities, and SSL technology.

# Sustainability

- Fusing technologies, CV toner, and innovative Sleep mode features help achieve low energy consumption.
- Help minimize waste with default twosided printing, Secure Print, and the ability to hold print jobs, preview them, and change print settings at the device.
- ENERGY STAR<sup>®</sup> certified and rated EPEAT<sup>®</sup> Gold.<sup>3</sup>

# Configuration



quality, and time-saving workflow

#### Main Unit

Туре

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store Optional: Fax

#### Processor

Canon Dual Custom Processor (Shared)

#### **Control Panel**

 Standard:
 10.1" TFT LCD WSVGA Color Touch-panel

 Optional:
 10.4" TFT LCD WSVGA Color Upright-panel

Memory

#### 4.0 GB RAM Hard Disk Drive

Standard: 250 GB/Maximum: 1 TB

#### Print Resolution

2400 dpi x 2400 dpi

#### Interface Connection

Network

Standard:	1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
Optional:	NFC, Bluetooth
Others	
Standard:	USB 2.0 x2 (Host), USB 3.0 x1 (Host),
	USB 2.0 x1 (Device)
Optional:	Serial Interface, Copy Control Interface

#### Paper Capacity (LTR, 20 lb. Bond)

Standard:3,550 SheetsMaximum:9,300 Sheets

## Paper Sources (LTR, 20 lb. Bond)

Standard:	Two 1,100-sheet Paper Drawers,
	Two 550-sheet Paper Cassettes,
	250-sheet Stack Bypass
Optional:	3,500-sheet Paper Deck (Paper Deck
	Unit-E1), 3,500-sheet Paper Deck (Pod
	Deck Lite-C1), 6,000-sheet Paper Deck
	(Multi-Drawer Paper Deck-C1)
Maximum:	9,300 Sheets (With Multi-Drawer Pape
	Deck-C1)

#### Paper Output Capacity (LTR, 20 lb. Bond)

250 Sheets (with Copy Tray-R2)

3,500 Sheets (with External Finisher-V2) 4,250 Sheets (with External Finisher-X1)

## **Finishing Capabilities**

Standard: Collate, Group With Finishers: Collate, Group, Offset, Staple, Booklet, Hole Punch, Staple-Free Staple, Staple On Demand, Document Insertion, Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold, Trimming

#### Supported Media Types

Drawers (1/2): Paper Cassettes (3/4):	Thin, Plain, Recycled, Color, Heavy, Pre-punched, Letterhead, Bond, Transparency Thin, Plain, Recycled, Color, Heavy, Pre-punched, Letterhead, Bond, Transparency, Tab, Envelope Thin, Plain, Recycled, Color, Heavy, Pre-punched, Labels, Letterhead, Bond, Coated, Transparency, Tab, Tracing, Envelope, Textured

# Supported Media Sizes

raper Diawers	
(1/2):	Letter
Paper	13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Cassettes (3/4):	Letter-R, Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (5-1/2" x 7-1/8" to 13" x 19-1/4"), Envelope Custom Size (3-1/8" x 5-7/8" to 13" x 19-1/4")
Stack Bypass:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (4" x 5-7/8" to 13" x 19-1/4"), Envelope Custom Size (3-1/2" x 3-7/8" to 13" x 19-1/4"), Free Size (4" x 7-1/8" to 13" x 19-1/4")

#### Supported Media Weights

Paper Drawers: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>) Paper Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)

 Stack Bypass:
 14 lb. Bond to 110 lb. Cover (52 to 220 g/m²)

 Duplexing:
 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

#### Print/Copy Speed (BW/Color)

R ADV 27580i:	Up to 80/70 ppm (Letter); Up to 60/52 ppm (Letter-R); Up to 47/41 ppm (Legal);
	Up to 40/35 ppm (11" x 17")
R ADV 27570i:	Up to 70/65 ppm (Letter); Up to 52/48 ppm (Letter-R); Up to 41/38 ppm (Legal); Up to 35/32 ppm (11" x 17")
R ADV 27565i:	Up to 65/60 ppm (Letter); Up to 48/45 ppm (Letter-R); Up to 38/35 ppm (Legal); Up to 32/30 ppm (11" x 17")

#### Warm-up Time

From Power On: 30 Seconds or Less Quick Startup Mode: 4 Seconds<sup>4</sup>

# Dimensions (W x D x H)

27-1/8" x 37-1/8" x 48" (689 mm x 941 mm x 1,220 mm)

#### Installation Space (W x D)

Basic [With Booklet Finisher-V2 (Stack Bypass and Cassette Drawers Open]]: 75-3/8" x 60" (1,913 mm x 1,524 mm) Fully Configured [With Multi-Drawer Paper Deck-C1+Document Insertion Unit-N1+Multi Function Professional Puncher-A1+Document Insertion Unit-N1+ Booklet Finisher-X1 (Cassette Drawers Open)]: 150-3/8" x 60" (3,818 mm x 1,524 mm)

#### Weight

Approx. 595.2 lb. (270 kg)⁵

## **Print Specifications**

**Data Processing Resolution** Up to 1200 dpi x 1200 dpi

# Standard Page Description Languages

UFR II, PCL<sup>®</sup>6, Adobe<sup>®</sup> PS<sup>®</sup> 3 **Direct Print** 

Available from USB, Advanced Box, Remote UI, and Web  $\mathsf{Access}^{\mathsf{6}}$ 

Supported File Types for Direct Print PDF, TIFF, JPEG, EPS,<sup>7</sup> XPS

# Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

#### Fonts

PCL Fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),® Barcode Fonts® PS Fonts: 136 Roman

#### Operating System<sup>10</sup>

UFR II:	Windows Vista®/Server 2008/Windows® 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/ Windows 10, MAC OS X (10.6.8 or later)
PCL:	Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/ Windows 10
PS:	Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/ Windows 10, MAC OS X (10.6.8 or later)

# Copy Specifications

First-Copy-Out Time (Letter)		
iR ADV	As fast as 4.4 seconds (BW)/	
C7580i:	5.4 seconds (Color)	
iR ADV	As fast as 4.8 seconds (BW)/	
C7570i:	5.9 seconds (Color)	
iR ADV	As fast as 4.8 seconds (BW)/	
C7565i:	5.9 seconds (Color)	
Copy Resolution		

Reading:	Up to 600 dpi x 600 dpi
Printing:	2400 dpi x 2400 dpi

#### Multiple Copies

Up to 9,999 copies

#### Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

## Preset Enlargements

121%, 129%, 200%, 400%

#### **Basic Copy Features**

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

#### **Special Copy Features**

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original, Color Balance, Adjust One-Touch Color, Area Designation

#### **Scan Specifications**

#### Туре

Color Platen and Single-pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity** 

300 Sheets (20 lb. Bond)

#### **Document Feeder Supported Media Sizes**

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

#### Document Feeder Supported Media Weights

3W Original:	13 lb. Bond to 80 lb. Cover
	(50 to 220 g/m²)
CL Original:	17 lb. Bond to 80 lb. Cover
	(64 to 220 g/m²)

#### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)] Pull Scan

Color Networ	k ScanGear2 for both Twain and WIA
Supported OS:	Windows Vista/7/8/8.1/10 Windows Server 2003/Server 2003 R2/ Server 2008/Server 2008 R2/Server
	2012/Server 2012 R2

#### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

#### Scan Speed (Letter) (300 dpi/600 dpi)

Single-sided Scanning (BW): 120 ipm/120 ipm Single-sided Scanning (Color): 120 ipm/70 ipm Double-sided Scanning (BW): 240 ipm/150 ipm Double-sided Scanning (Color): 220 ipm/90 ipm

#### Send Specifications

#### Destination

Optional:

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

#### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

#### Send Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100dpi

#### **Communication Protocol**

File:	FTP, SMB, WebDAV
E-mail/I-Fax:	SMTP, POP3, I-Fax (Simple, Full)
File Format	
Standard:	TIFF, JPEG, PDF(Compact, Searchabl

1:	TIFF, JPEG, PDF(Compact, Searchable,
	Apply policy, Optimize for Web, PDF
	A/1-b), XPS (Compact, Searchable),
	Office Open XML (PowerPoint®, Word)
	PDF (Trace & Smooth, Encrypted),
	PDF/XPS (Digital Signature)

#### **Universal Send Features**

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

#### **Fax Specifications**

#### Maximum Number of Connection Lines

Modem Speed

Super G3: 33.6 Kbps G3: 14.4 Kbps

#### **Compression Method** MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

#### Sending/Recording Size Statement-R to 11" x 17"

Fax Memory

Up to 30,000 pages Speed Dials

# Max. 200

Group Dials/Destinations

Max. 199 dials

Sequential Broadcast

Max. 256 addresses

Memory Backup

# Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

#### **Store Specifications**

#### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

#### Advanced Box

Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.) SMB: 64 WebDAV: 3 (Active Sessions)





As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the EDERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Google Cloud Print<sup>™</sup> is etiher a registered trademark or trademarks of Google Inc. AirPrint and the AirPrint logo are trademarks of Apple Inc. Adobe® and PostScript<sup>®</sup> 3<sup>™</sup> are either registered trademarks or trademarks of trademarks of trademarks of trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft<sup>®</sup> and PowerPoint<sup>®</sup> are either registered trademarks of trademarks of Microsoft Corporation in the United States and/or other countries. PCL<sup>®</sup> is a registered trademark of Hewlett-Packard Company. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



Typical Electricity Consumption (TEC) Rating C7580i: 5.5 kWh

C7570i: 4.6 kWh C7565i: 4.5 kWh

## Standards

Advanced Box Available Disk Space

Advanced Box Features

Security Specifications

Memory Media

Authentication

Standard

Optional:

Standard

Optional

Network

Standard

Document

Standard

Optional:

C7580i

C7580i:

Maximum

C7580i:

Standby:

Sleep Mode:

C7570i/7565i:

Plug (Main Unit)

Power Consumption

Data

Standard: USB

Approx. 16 GB (Standard HDD)/Approx. 480 GB (1 TB HDD)

Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Universal Login Manager, User

Authentication, Department ID

Management System, Device and Function Level Log-in

Trusted Platform Module (TPM),

Drive Erase, Mail Box Password

Criteria Certification, Data Loss

Prevention (Requires uniFLOW)

Hard Disk Password Lock Hard Disk

Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)

Hard Disk Drive Mirroring, Hard Disk Drive Removal, IEEE 2600.2 Common

IP/Mac Address Filtering, IPsec, TLS

POP Authentication before SMTP

Secure Print, Forced Hold Printing,

ES2.5 Integration

208 V AC, 60 Hz,12 A

NEMA 6-15P

Approx. 2.5 kWh

Approx. 119.2 W

Approx. 0.9 W<sup>11</sup>

120-127 V AC, 60 Hz,16 A

**Environmental Specifications** 

**Power Requirements** 

C7570i/7565i: NEMA 5-20P

C7570i/7565i: Approx. 2.0 kWh

Adobe LiveCycle® Rights Management

Encrypted PDF, Encrypted Secure Print,

User and Device Signatures, Secure

Watermarks, Document Scan Locking

Encrypted Communication, SNMP V3.0,

IEEE 802.1X, IPv6, SMTP Authentication,

Authentication, Access

uniFLOW

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search

ENERGY STAR® Certified Rated EPEAT® Gold<sup>3</sup> RoHS Compliant

# Consumables

# Toner

GPR-56 Toner

#### Toner Yield (Estimated @ 5% Coverage)

Black: 82,000 Images Color (C,M,Y): 66,500 Images

#### Footnotes

- <sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
   <sup>2</sup> Canon offers security features that can help your business.
- Many variables can impact the security of your devices and data. Canon does not warrant that the use of its features will prevent malicious attacks, or prevent misuse of devices or data or other security issues. Nothing herein should be construed as legal counsel or regulatory advice concerning customers' compliance with laws related to privacy and security. Customers must have their own qualified counsel determine the feasibility of a particular solution as it relates to regulatory and statutory compliance. Some security settings may affect device functionality or performance. You may want to test these settings before deploying them in your environment to ensure you understand their effects.
- <sup>3</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- <sup>4</sup> Time from device power-on to when copy jobs can be programmed.
- <sup>5</sup> Includes main unit, ADF, and consumables.
- <sup>6</sup> PDF print from Web sites is supported.
- <sup>7</sup> EPS can be printed directly only from the Remote User Interface.
- <sup>8</sup> Requires the optional PCL International Font Set-A1.
- <sup>9</sup> Requires the optional Barcode Printer Kit-D1
- <sup>10</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- <sup>10</sup> 0.9 W Sleep mode is not available in all circumstances due to certain settings.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C7500 Series Specifications document.







